


NMHA5326

5MP Megapixel Starlight H.265 IP Camera Module



- SONY 1/2.9" IMX326 CMOS sensor
- 5 Megapixels
- Starlight series with supreme low light performance
- Video codec: H.265, H.264, MJPEG
- Simultaneously triple video streaming
- True HDR
- Power over Ethernet (optional)
- Supporting ONVIF Profile S

SPECIFICATIONS

System on Chip (SoC)	Hi3516A V100
Image Sensor	SONY 1/2.9" IMX326 CMOS with 3072 x 2160 resolution
Lens	Not included
DC-iris	Supported
Minimum Illumination	0.03 Lux/F1.2 (color); 0.005 Lux/F1.2 (B/W)
HDR	True HDR, 90dB
Video Codec	H.265, H.264, MJPEG
Resolutions	2592 x 1944 to 480 x 272
Frame Rate	Up to 30 fps in 2592 x 1944 resolution
Video Streaming	Supporting triple streaming simultaneously
Rate Control	VBR, CBR, fixed QP
Standards	ONVIF Profile S
Memory	256 MB RAM, 16 MB flash
Network Interface	100 Mbps Ethernet
Internet Protocols	IPv4, IPv6, ICMP, IGMP, QoS, TCP, UDP, DHCP, DNS, DDNS, mDNS, zeroconf, HTTP, HTTPS, NTP, RTP, RTCP, RTSP, TLS, UPnP, ARP
Internet Protocols (optional)	FTPS, RTMP, SIP, SMB/CIFS, SMTP, SNMPv3, WebRTC, P2P, 802.1X, PPPoE
Audio Coding	G.711 PCM, G.726 ADPCM, MP3 (optional), AAC LC (optional)
Audio Interface	Microphone in, line out
System Integration	1 alarm in, 1 alarm out
Power Source	DC 12V, Power over Ethernet (optional)
Power Consumption	Typical 2.8W
Operation Conditions	-20~50°C
Dimensions (L x W x H)	38mm*38mm*9.5mm
Weight	26g

*Specifications may be subject to change without prior notice.